

SpecFlow

Premium self-leveling underlayment

A cement based, non-shrinking, self-leveling floor underlayment designed for interior use. This single component product produces a smooth subfloor that will accept floor coverings in as little as 12 - 18 hours after installation. Just mix SpecFlow with water, pour or pump, and it will seek its own level to produce a smooth, flat, hard surface.

BENEFITS

- When properly mixed, produces a flowable underlayment with a flow time of 20 minutes at 70°F
- Can be featheredged without fear of chipping or spalling
- Self-leveling, requiring no troweling
- Can be pumped
- Produces a smooth, blemish free surface, requiring no grinding or sanding
- Compatible with subsequent adhesives for carpet, tile and the like

USAGE

- Unlevel floors
- Repair of old, worn concrete that will receive decorative topping
- Concrete sub-flooring

PACKAGING

- 50 lb bag
- Coverage: approx 24 sq-ft @ 1/4"



CONTACT YOUR SPECHEM PROFESSIONAL FOR MORE INFORMATION.

SpecFlow

Premium self-leveling underlayment



TYPICAL TEST DATA

Set Time at 70°F (ASTM C-266)	
Initial Set	50 min
Final Set	80 min
Compressive Strength (ASTM C-109)	
1 Day	3000 psi
7 Days	4500 psi
28 Days	5500 psi
Bond Strength (ASTM C-882 modified)	
14 day w/SpecPrime	1000 psi
Flexural Strength (ASTM C-348)	
28 Days	1150 psi
Yield	
Yield per bag	.50 cu-ft (125 lbs/cuft)



CONTACT YOUR SPECHEM PROFESSIONAL FOR MORE INFORMATION.