

## Fast-setting polymer-modified concrete repair material

A general purpose polymer-modified concrete repair mortar for concrete floors, walls, precast, tilt-up and masonry surfaces. SpecPatch 5 can be used for horizontal, vertical, and overhead applications to provide a durable repair that can be shaped by shaving or sanding.



### ✓ Benefits

- Can be featheredged
- Lifts up to 1" in thickness
- 5 minute set time for quick turn around
- Can be shaped
- Excellent durability and adhesion
- Dries to color of concrete



## Usage

- Interior & exterior
- Vertical, overhead & horizontal repairs
- Used at no-slump consistency
- Outstanding repair material for concrete pipe, curbs, sidewalks, formed and precast concrete



## Packaging

- 50 lb bag
- Coverage: approx 20 sq-ft @ 1/4"

## TYPICAL TEST DATA

Set Time at 70°F (ASTM C-266)	
Initial Set	5 min
Final Set	8 min
Compressive Strength (ASTM C-109)	
1 Day	3150 psi
7 Days	5000 psi
28 Days	6500 psi
Freeze-Thaw (ASTM C-672)	
Scaling Resistance	25 cycles = 0% loss
Flexural Strength (ASTM C-348)	
7 Days	500 psi
28 Days	650 psi
Yield	
Yield per bag	.43 cu-ft