

SpecPoxy Coating Clear Part A

Version 1

pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

1.1 Trade Name (as labeled):	SpecPoxy Coating Clear Part A
Synonyms:	N/A
CAS No:	Mixture
1.2 Product Use:	Epoxy bonding adhesive
1.3 Company Name:	SpecChem
Company Address:	1511 Baltimore Ave; Suite 600
Company Address Cont:	Kansas City, MO 64108
Business Phone:	(816) 968-5600
Website:	www.specchemllc.com
1.4 Emergency Telephone Number:	Chemtrec: (800) 424-9300
Date of Last Revision:	March 9, 2015
Date of Current Revision:	July 1, 2018

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a clear to amber colored liquid with a characteristic odor.

Health Hazards: May cause skin and eye irritation. Contact with skin may cause allergic reaction.

Flammability Hazards: This product is not a flammable liquid.

Reactivity Hazards: None.

Environmental Hazards: The environmental effects of this product have not been investigated, however release may cause long term adverse environmental effects.

US DOT Symbols:

Not Regulated



EU and GHS Symbols:

Signal Word:

Warning

2.1 EU Labeling and Classification:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

EU HAZARD CLASSIFICATION OF INGREDIENTS PER DIRECTIVE 1272/2008/EC:

Index Number:

500-033-5 is listed in Annex I 603-074-00-8

218-645-3 is listed in Annex I 603-056-00-X

Substances not listed either individually or in group entries must be self classified.

Components Contributing to Classification:

Bisphenol A Diglycidyl Ether Resin, Glycidyl 2-methylphenyl Ether

2.2 Label Elements:

GHS Hazard Classifications:

Skin Irritation Category 2

Skin Sensitization Category 1

SpecPoxy Coating Clear Part A

Version 1

pg. 2

Hazard Statements:

Eye Irritant Category 2
Germ Cell Mutagenicity Category 2
Chronic Aquatic Toxicity Category 2
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H341 Suspected of causing genetic defects
H411 Toxic to aquatic life with long lasting effects

Precautionary Statements:

P280 Wear protective gloves/eye protection/face protection.
P264 Wash thoroughly after handling.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated clothing should not be allowed out of the workplace.

Response Statements:

P273 Avoid release to the environment
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P311 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P391 Collect spillage.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Storage Statements:

Disposal Statements:

2.3 Health Hazards or Risks From Exposure:

Symptoms of Overexposure by Route of Exposure:

The most significant routes of overexposure for this product are by contact with skin or eyes. The symptoms of overexposure are described in the following paragraphs.

Acute:

Inhalation: May cause respiratory tract irritation. May cause headaches, drowsiness, or dizziness.

Skin Contact: May be irritating to skin. Contact with skin may cause allergic reaction.

Eye Contact: May cause irritation to the eyes.

Ingestion: May be harmful if swallowed. May cause nausea or diarrhea.

Chronic: Not known.

Target Organs:

Acute: Eyes, Skin

Chronic: Not known.

SpecPoxy Coating Clear Part A

Version 1

pg. 3

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.	EINECS No.	Hazard Classification
Bisphenol A Diglycidyl Ether Resin	60-70%	25068-38-6	500-033-5	Skin Irrit. 2, Skin Sens. 1, Eye Irrit. 2, Aquatic Chronic 2
Glycidyl 2-methylphenyl Ether	5-10%	2210-79-9	218-645-3	Skin Irrit. 2, Skin Sens. 1, Muta. 2, Aquatic Chronic 2
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).				

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES

4.1 Description of First Aid Measures:

Eye Contact:	If product enters the eyes, flush with plenty of water or eye wash solution for several minutes. Remove contacts if present and easy to do. Seek medical attention if irritation persists.
Skin Contact:	Wash skin thoroughly with soap and water after handling. Seek medical attention if irritation develops and persists.
Inhalation:	If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.
Ingestion:	If product is swallowed, call physician or poison center immediately. If professional advice is not available, do not induce vomiting. Never induce vomiting or give dilutents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

Medical Conditions
Generally Aggravated
By Exposure:

Pre-existing skin, respiratory system or eye problems may be aggravated by prolonged contact.

4.2 Symptoms and Effects Both Acute and Delayed: Exposure to the eyes may cause irritation.

4.3 Recommendations to Physicians: Treat symptoms and eliminate overexposure.

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Fire Extinguishing Materials:

Use the following fire extinguishing materials: **Water Spray: Yes**

SpecPoxy Coating Clear Part A

Version 1

pg. 4

Foam: Yes
Halon: Yes
Carbon Dioxide: Yes
Dry Chemical: Yes
Other: Any "C" Class

5.2 Unusual Fire and Explosion Hazards:

Irritating and toxic fumes may be produced at high temperatures. Use of water may result if the formation of a toxic aqueous solution. Do not allow run-off from fire fighting to enter drains or water courses.

Explosive Sensitivity to Mechanical Impact: No
 Explosive Sensitivity to Static Discharge: No

5.3 Special Fire-Fighting Procedures:

- Incipient fire responders should wear eye protection.
- Structural firefighters must wear Self-Contained Breathing Apparatus (SCBA) and full protective equipment.
- Isolate materials not yet involved in the fire and protect personnel.
- Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray.
- If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas.

NFPA RATING SYSTEM		HMIS RATING SYSTEM													
Flammability Health Reactivity Other		HAZARDOUS MATERIAL IDENTIFICATION SYSTEM <table border="1"> <tr> <td style="background-color: #00aaff; color: white;">HEALTH HAZARD (BLUE)</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: #ff0000; color: white;">FLAMMABILITY HAZARD (RED)</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: #ffff00; color: black;">PHYSICAL HAZARD (YELLOW)</td> <td style="text-align: center;">0</td> </tr> </table>		HEALTH HAZARD (BLUE)	2	FLAMMABILITY HAZARD (RED)	1	PHYSICAL HAZARD (YELLOW)	0						
HEALTH HAZARD (BLUE)	2														
FLAMMABILITY HAZARD (RED)	1														
PHYSICAL HAZARD (YELLOW)	0														
<table border="1"> <thead> <tr> <th colspan="4">PROTECTIVE EQUIPMENT</th> </tr> <tr> <th>EYES</th> <th>RESPIRATORY</th> <th>HANDS</th> <th>BODY</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">See Sect 8</td> <td style="text-align: center;"></td> <td style="text-align: center;">See Sect 8</td> </tr> </tbody> </table>				PROTECTIVE EQUIPMENT				EYES	RESPIRATORY	HANDS	BODY		See Sect 8		See Sect 8
PROTECTIVE EQUIPMENT															
EYES	RESPIRATORY	HANDS	BODY												
	See Sect 8		See Sect 8												
For Routine Industrial Use and Handling Applications Hazard Scale: 0 = Minimum 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic Hazard															

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Use cautious judgment when cleaning up spill. Wear suitable protective clothing, gloves, and eye/face protection.

SpecPoxy Coating Clear Part A

Version 1 pg. 5

6.2 Environmental Precautions:

Construct a dike to prevent spreading. Keep out of sewers, storm drains, surface waters, and soils.

6.3 Spill and Leak Response:

Small Spills:

- Collect material via broom or mop. Place in tightly sealed containers for proper disposal.
- Approach spill areas with caution.
- If liquid was introduced, create a dike or trench to contain material.
- Soak up with absorbent material such as clay, sand or other suitable non-reactive material.

Large Spills:

- Place in leak-proof containers. Seal tightly for proper disposal.
- Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

To prevent eye contact under the foreseeable conditions of use, wear appropriate safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Do not handle or store near heat, sparks, or flame.

7.2 Storage and Handling Practices:

Keep away from incompatible materials. Keep container closed when not in use and store in well ventilated area.

7.3 Specific Uses:

Epoxy.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Ingredients	CAS No.	OSHA PEL	NIOSH PEL
Bisphenol A Diglycidyl Ether Resin	25068-38-6	Not Listed	Not Listed
Glycidyl 2-methylphenyl Ether	2210-79-9	Not Listed	Not Listed

8.2 Exposure Controls:

Ventilation and Engineering Controls:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

SpecPoxy Coating Clear Part A

Version 1

pg. 6

Respiratory Protection:

Not required for properly ventilated areas. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

Eye Protection:

Safety glasses or goggles are required. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

Hand Protection:

Chemical resistant gloves are required to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards. Use body protect appropriate to task being performed.

Body Protection:

If necessary, refer to appropriate Standards of Canada, or appropriate standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on Basic Physical and Chemical Properties:****Appearance (Physical State and Color):** Clear to amber liquid**Odor:** Characteristic**Odor Threshold:** No data available**pH:** No data available**Melting/Freezing Point:** No data available**Boiling Point:** 300°F (148.9°C)**Flash Point:** 200°F (93°C)**Evaporation Rate:** No data available**Flammability (Solid; Gas):** Not applicable**Upper/Lower Flammability or Explosion Limits:** No data available**Vapor Pressure (mm Hg @ 20°C (68° F):** No data available

SpecPoxy Coating Clear Part A

Version 1 pg. 7

Vapor Density: No data available
Relative Density: No data available
Specific Gravity: 1.1
Solubility in Water: Not miscible
Weight per Gallon: No data available
Partition Coefficient (n-octanol/water): No data available
Auto-Ignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: No data available
9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY

10.1 Reactivity: This product is not reactive.
10.2 Stability: Stable under conditions of normal storage and use.
10.3 Possibility of Hazardous Reactions: Will not occur.
10.4 Conditions to Avoid: Heat, open flame or other sources of ignition..
10.5 Incompatible Substances: Strong oxidizing agents..
10.6 Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide and other decomposition products can occur during combustion if not use according to specifications.

SECTION 11 – TOXICOLOGY INFORMATION

11.1 Information on Toxicological Effects:
Toxicity Data:

Bisphenol A Diglycidyl Ether Resin	25068-38-6	LD50 Oral – Rat	13,600 mg/kg
Glycidyl 2-methylphenyl Ether	2210-79-9	LD50 Oral – Rat	4,000 mg/kg

Suspected Cancer Agent: Ingredients within this product are not found on one or more of the following lists: FEDERAL OSHA Z LIST, NTP, IARC, or CAL/OSHA and therefore are not considered to be cancer-causing agents by these agencies.
Irritancy: Skin, eye irritant.
Sensitization to the Product: This product is not expected to cause skin sensitization.
Germ Cell Mutagenicity: This product does not contain ingredients that are suspected to be a germ cell mutagenic.
Reproductive Toxicity: No data available.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 Toxicity:

Bisphenol A Diglycidyl Ether Resin	25068-38-6	LC50 – Rainbow Trout	<10 mg/l – 96h
		EC50 – Algae	<10 mg/l – 96h
Glycidyl 2-methylphenyl Ether	2210-79-9	LC50 – Fish	2.8-5.1 mg/l – 96h

SpecPoxy Coating Clear Part A

Version 1 pg. 8

<p>12.2 Persistence and Degradability:</p> <p>12.3 Bioaccumulative Potential:</p> <p>12.4 Mobility in Soil:</p> <p>12.5 Results of PBT and vPvB Assessment:</p> <p>12.6 Other Adverse Effects:</p> <p>12.7 Water Endangerment Class:</p>	<p>No specific data available on this product.</p> <p>No specific data available on this product.</p> <p>No specific data available on this product.</p> <p>No specific data available on this product.</p> <p>No data available</p> <p>At present, there are no ecotoxicological assessments for this product.</p>
--	---

SECTION 13 – DISPOSAL CONSIDERATIONS

<p><u>13.1 Waste Treatment Methods:</u></p> <p><u>13.2 EU Waste Code:</u></p>	<p>Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Australia, EU Member States and Japan.</p> <p>Not determined</p>
--	--

SECTION 14 - TRANSPORTATION INFORMATION

<p><u>14.1 U.S. Department of Transportation (DOT) Shipping Regulations:</u></p> <p><i>This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.</i></p>	
<p>UN Identification Number:</p> <p>Proper Shipping Name:</p> <p>Hazard Class Number and Description:</p> <p>Packing Group:</p> <p>DOT Label(s) Required:</p> <p>North American Emergency Response Guidebook Number:</p>	<p>Not Regulated</p> <p>None</p> <p>None</p> <p>None</p> <p>None</p> <p>None</p>
<p><u>14.2 Environmental Hazards:</u></p>	
<p>Marine Pollutant:</p> <p><u>14.3 Special Precaution for User:</u></p> <p><u>14.4 International Air Transport Association Shipping Information (IATA):</u></p> <p><u>14.5 International Maritime Organization Shipping Information (IMO):</u></p>	<p>The components of this product are designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).</p> <p>None</p> <p>This product is considered as dangerous goods.</p>
<p>UN Identification Number:</p> <p>Proper Shipping Name:</p> <p>Hazard Class Number and Description:</p> <p>Packing Group:</p> <p>EMS-No:</p>	<p>Not regulated</p> <p>None</p> <p>None</p> <p>None</p> <p>None</p>

SpecPoxy Coating Clear Part A

Version 1

pg. 9

SECTION 15 – REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations Specific for the Substance or Mixture:

United States Regulations:

U.S. SARA Reporting Requirements:

The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA 311/312:

Acute Health: Yes; Chronic Health: No; Fire: No; Reactivity: No

U.S. CERCLA Reportable Quantity:

Not Applicable

U.S. TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory or are exempted from listing.

Other U.S. Federal Regulations:

None known

California Safe Drinking Water and Toxic Enforcement Act (Proposition 66):

This product does not contain ingredients on the Proposition 65 Lists.

15.2 Canadian Regulations:

Canadian DSL/NDSL Inventory Status:

Components are DSL Listed, NDSL Listed and/or are exempt from listing

Other Canadian Regulations:

Not applicable

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian WHMIS Classification and Symbols:

This product is Class D2A, Materials causing other toxic effects, per WHMIS Controlled Product Regulations.



15.3 European Economic Community Information:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. See Section 2 for Details.

Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 Australian Information for Product:

Components of this product are listed on the International Chemical Inventory list.

15.5 Japanese Information for Product:

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 International Chemical Inventories:

Listing of the components on individual country Chemical Inventories is as follows:

Australian Inventory of Chemical Substances (AICS): Listed

SpecPoxy Coating Clear Part A

Version 1

pg. 10

Korean Existing Chemicals List (ECL): Listed
Japanese Existing National Inventory of Chemical Substances (ENCS): Listed
Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed
U.S. TSCA: Listed

SECTION 16 – OTHER INFORMATION

Prepared By: Chris Eigbrett (MSDS to GHS Compliance)
Date of Printing: July 1, 2018

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET

SpecPoxy Coating Part B

Version 1

pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

1.1 Trade Name (as labeled):	SpecPoxy Coating Part B
Synonyms:	N/A
CAS No:	Mixture
1.2 Product Use:	Epoxy bonding adhesive
1.3 Company Name:	SpecChem
Company Address:	1511 Baltimore Ave; Suite 600
Company Address Cont:	Kansas City, MO 64108
Business Phone:	(816) 968-5600
Website:	www.specchemllc.com
1.4 Emergency Telephone Number:	Chemtrec: (800) 424-9300
Date of Last Revision:	March 9, 2015
Date of Current Revision:	July 1, 2018

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a gray colored liquid with a characteristic odor.

Health Hazards: May cause skin, eye and respiratory system irritation. Inhalation may cause drowsiness or dizziness. Contact with skin may cause allergic reaction.

Flammability Hazards: This product is a non-flammable liquid.

Reactivity Hazards: None.

Environmental Hazards: The environmental effects of this product have not been investigated, however release may cause long term adverse environmental effects.



EU and GHS Symbols:

Signal Word:

Danger

Components Contributing to Classification:

Benzyl Alcohol, 2,4,6-tris(dimethylaminomethyl)phenol, isophorodiamine 1, 2-, Ethanediamine N₁, N₂-bis, Ethanediamine N₁-(2-aminoethyl), tetraethylenepentamine, bis[(dimethylamino)methyl]phenol

2.2 Label Elements:

GHS Hazard Classifications:

Acute oral, dermal, and inhalation toxicity, Category 4.
 Eye Damage, Category 1.
 Skin Corrosive, Category 1B.
 Skin Sensitizer, Category 1.
 Hazardous to the aquatic environment, long-term, chronic, Category 3.

SpecPoxy Coating Part B

Version 1

pg. 2

Hazard Statements:

H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H413 - May cause long lasting harmful effects to aquatic life.

Precautionary Statements:

P260 - Do not breathe dusts or mists.

P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink, or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release into the environment.

P280 - Wear protective gloves/eye protection/face protection.

P301+P330+P312 IF SWALLOWED: Rinse mouth. Do not induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor if you feel unwell.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with Local, State, Federal, and Provincial regulations.

Storage Statements:

Disposal Statements:

2.3 Health Hazards or Risks From Exposure:

Symptoms of Overexposure by Route of Exposure:

The most significant routes of overexposure for this product are by contact with skin or eyes. The symptoms of overexposure are described in the following paragraphs.

Acute:

Inhalation: May cause respiratory tract irritation. May cause headaches, drowsiness, or dizziness.

Skin Contact: A single prolonged exposure may result in the absorption of harmful amounts. May cause burns or redness.

Contact with skin may cause allergic reaction.

Eye Contact: Corrosive material may cause irritation with possible burns and tissue damage.

Ingestion: Harmful if swallowed. May cause nausea and diarrhea.

SpecPoxy Coating Part B

Version 1

pg. 3

Chronic: Repeated exposure may cause skin dryness or cracking.

Target Organs:

Acute: Skin, Eyes

Chronic: Skin.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.	EC Num.
Benzyl Alcohol	30-60%	100-51-6	202-859-9
Cycloaliphatic Amine Adduct	10-30%	68609-08-5	
Isophoronediamine	10-20%	2855-13-2	220-666-8
1,2-Ethanediamine, N ₁ , N ₂ -bis(2-aminoethyl)	<1%	112-24-3	203-950-6
1,2-Ethanediamine, N ₁ -(2-aminoethyl), N ₂ –[2-[(2-aminoethyl)amino]ethyl]-	<25-40%	112-57-2	203-986-2
Amines, polyethylenepoly-	<15%	68131-73-7	268-626-9

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES

4.1 Description of First Aid Measures:

Eye Contact: If product enters the eyes, flush with plenty of water or eye wash solution for several minutes. Remove contacts if present and easy to do. Seek medical attention if irritation persists.

Skin Contact: Wash skin thoroughly with soap and water after handling. Seek medical attention if irritation develops and persists.

Inhalation: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

Ingestion: If product is swallowed, call physician or poison center immediately. If professional advice is not available, do not induce vomiting. Never induce vomiting or give dilutents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or SDS with the victim to the health professional.

**Medical Conditions
Generally Aggravated
By Exposure:**

Pre-existing skin, respiratory system or eye problems may be aggravated by prolonged contact.

4.2 Symptoms and Effects Both Acute and Delayed: Exposure to skin and eyes may cause burns or redness.

4.3 Recommendations to Physicians: Treat symptoms and eliminate overexposure.

SpecPoxy Coating Part B

Version 1 pg. 4

SECTION 5 – FIRE FIGHTING MEASURES

5.1 Fire Extinguishing Materials:

Use the following fire extinguishing materials:

- Water Spray:** Yes
- Foam:** Yes
- Halon:** Yes
- Carbon Dioxide:** Yes
- Dry Chemical:** Yes
- Other:** Any “C” Class

5.2 Unusual Fire and Explosion Hazards:

Irritating and toxic fumes may be produced at high temperatures. Use of water may result if the formation of a toxic aqueous solution. Do not allow run-off from fire fighting to enter drains or water courses.

Explosive Sensitivity to Mechanical Impact: No
 Explosive Sensitivity to Static Discharge: No

5.3 Special Fire-Fighting Procedures:

- Incipient fire responders should wear eye protection.
- Structural firefighters must wear Self-Contained Breathing Apparatus (SCBA) and full protective equipment.
- Isolate materials not yet involved in the fire and protect personnel.
- Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray.
- If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas.

<p style="text-align: center;">NFPA RATING SYSTEM</p> <p style="text-align: center;">Flammability</p> <div style="text-align: center;"> </div> <p style="text-align: center;">Other</p> <p style="text-align: center;">Health Reactivity</p>	<p style="text-align: center;">HMIS RATING SYSTEM</p> <p style="text-align: center;">HAZARDOUS MATERIAL IDENTIFICATION SYSTEM</p> <table style="width: 100%; border-collapse: collapse;"> <tr style="background-color: #00b0f0; color: white;"> <td style="padding: 2px;">HEALTH HAZARD (BLUE)</td> <td style="text-align: center; padding: 2px;">3</td> </tr> <tr style="background-color: #ff0000; color: white;"> <td style="padding: 2px;">FLAMMABILITY HAZARD (RED)</td> <td style="text-align: center; padding: 2px;">1</td> </tr> <tr style="background-color: #ffff00; color: black;"> <td style="padding: 2px;">PHYSICAL HAZARD (YELLOW)</td> <td style="text-align: center; padding: 2px;">0</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr style="background-color: #cccccc;"> <th colspan="4" style="text-align: center; padding: 2px;">PROTECTIVE EQUIPMENT</th> </tr> <tr style="font-size: small;"> <th style="width: 25%; padding: 2px;">EYES</th> <th style="width: 25%; padding: 2px;">RESPIRATORY</th> <th style="width: 25%; padding: 2px;">HANDS</th> <th style="width: 25%; padding: 2px;">BODY</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 5px;"></td> <td style="text-align: center; padding: 5px;">See Sect 8</td> <td style="text-align: center; padding: 5px;"></td> <td style="text-align: center; padding: 5px;">See Sect 8</td> </tr> </tbody> </table> <p style="text-align: center; font-size: x-small;">For Routine Industrial Use and Handling Applications</p> <p style="text-align: center; font-size: x-small;">Hazard Scale: 0 = Minimum 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic Hazard</p>	HEALTH HAZARD (BLUE)	3	FLAMMABILITY HAZARD (RED)	1	PHYSICAL HAZARD (YELLOW)	0	PROTECTIVE EQUIPMENT				EYES	RESPIRATORY	HANDS	BODY		See Sect 8		See Sect 8
HEALTH HAZARD (BLUE)	3																		
FLAMMABILITY HAZARD (RED)	1																		
PHYSICAL HAZARD (YELLOW)	0																		
PROTECTIVE EQUIPMENT																			
EYES	RESPIRATORY	HANDS	BODY																
	See Sect 8		See Sect 8																

SpecPoxy Coating Part B

Version 1

pg. 5

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)
6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Use cautious judgment when cleaning up spill. Wear suitable protective clothing, gloves, and eye/face protection.

6.2 Environmental Precautions:

Construct a dike to prevent spreading. Keep out of sewers, storm drains, surface waters, and soils.

6.3 Spill and Leak Response:
Small Spills:

- Collect material via broom or mop. Place in tightly sealed containers for proper disposal.
- Approach spill areas with caution.
- If liquid was introduced, create a dike or trench to contain material.
- Soak up with absorbent material such as clay, sand or other suitable non-reactive material.

Large Spills:

- Place in leak-proof containers. Seal tightly for proper disposal.
- Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada and its Provinces, those of Australia, Japan and EU Member States (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING AND STORAGE
7.1 Precautions for Safe Handling:

To prevent eye contact under the foreseeable conditions of use, wear appropriate safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Do not handle or store near heat, sparks, or flame.

7.2 Storage and Handling Practices:

Keep away from incompatible materials. Keep container closed when not in use and store in well ventilated area.

7.3 Specific Uses:

Epoxy.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION
8.1 Exposure Parameters:

Hazardous Ingredients	CAS No.	OSHA PEL	NIOSH PEL
Benzyl Alcohol	100-51-6	Not listed	Not listed
Cycloaliphatic Amine Adduct	68609-08-5	Not listed	Not listed
Isophoronediamine	2855-13-2	Not listed	Not listed
1,2-Ethanediamine, N ₁ , N ₂ -bis(2-aminoethyl)	112-24-3	Not listed	Not listed
1,2-Ethanediamine, N ₁ -(2-aminoethyl), N ₂ -[2-[(2-aminoethyl)amino]ethyl]-	112-57-2	Not listed	Not listed
Amines, polyethylenepoly-	68131-73-7	Not listed	Not listed

SpecPoxy Coating Part B

Version 1

pg. 6

8.2 Exposure Controls:

Ventilation and Engineering Controls:

Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

Respiratory Protection:

Not required for properly ventilated areas. Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

Eye Protection:

Safety glasses or goggles are required. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian Standards, and the European Standard EN166, Australian Standards, or relevant Japanese Standards.

Hand Protection:

Chemical resistant gloves are required to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138, the European Standard DIN EN 374, the appropriate Standards of Canada, Australian Standards, or relevant Japanese Standards.

Body Protection:

Use body protect appropriate to task being performed. If necessary, refer to appropriate Standards of Canada, or appropriate standards of the EU, Australian Standards, or relevant Japanese Standards. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

SpecPoxy Coating Part B

Version 1

pg. 7

9.1 Information on Basic Physical and Chemical Properties:

Appearance (Physical State and Color): Gray liquid
Odor: Characteristic
Odor Threshold: No data available
pH: No data available
Melting/Freezing Point: No data available
Boiling Point: 300°F (148.9°C)
Flash Point: 212°F (100°C)
Evaporation Rate: No data available
Flammability (Solid; Gas): Not applicable
Upper/Lower Flammability or Explosion Limits: No data available
Vapor Pressure (mm Hg @ 20°C (68° F): No data available
Vapor Density: No data available
Relative Density: No data available
Specific Gravity: 1.0 ± 0.05
Solubility in Water: Slightly soluble
Weight per Gallon: No data available
Partition Coefficient (n-octanol/water): No data available
Auto-Ignition Temperature: No data available
Decomposition Temperature: No data available
Viscosity: No data available
9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY

<u>10.1 Reactivity:</u>	This product is not reactive.
<u>10.2 Stability:</u>	Stable under conditions of normal storage and use.
<u>10.3 Possibility of Hazardous Reactions:</u>	Will not occur.
<u>10.4 Conditions to Avoid:</u>	Heat, open flame or other sources of ignition.
<u>10.5 Incompatible Substances:</u>	Strong oxidizing agents.
<u>10.6 Hazardous Decomposition Products:</u>	Carbon monoxide, Carbon dioxide and other decomposition products can occur during combustion if not use according to specifications.

SECTION 11 – TOXICOLOGY INFORMATION

11.1 Information on Toxicological Effects:

Benzyl Alcohol:	
RTECS Number:	DN3150000
Skin:	Administration onto the skin – Rabbit LD50 – Lethal dose, 50 percent kill: 2000 mg/kg [Details of toxic effects not reported other than lethal dose value]. Administration onto the skin – Rabbit Standard Draize test: 100 mg/24H [Moderate] (RTECS)
Inhalation:	Inhalation – Mouse LC50 – Lethal concentration, 50 percent kill: >500 mg/m3 [Behavioral – Somnolence (general depressed activity) Behavioral – Ataxia Lungs, Thorax, or Respiration – Respiratory depression] Inhalation – Rat LC50 – Lethal concentration, 50 percent kill: >500 mg/m3 [Behavioral – Somnolence (general depressed

SpecPoxy Coating Part B

Version 1

pg. 8

Ingestion: activity) Behavioral – Ataxia lungs, thorax, or respiration – respiratory depression] (RTECS).
 Oral – Rat LD50 – Lethal Dose, 50 percent kill: 1230 mg/kg [Behavioral – somnolence (general depressed activity) Behavioral – Excitement Behavioral – Coma]
 Oral – Mouse LD50 – Lethal dose, 50 percent kill: 1360 mg/kg [Details of toxic effect not reported other than lethal does value]
 Oral – Rabbit LD50 – Lethal dose, 50 percent kill: 1040 mg/kg [Behavioral – Somnolence (general depressed activity)]
 Oral – Rat LD50 – Lethal dose, 50 percent kill: 1660 mg/kg [Behavioral – somnolence (general depressed activity) Behavioral – Ataxia Lungs, Thorax, or Respiration – Respiratory depression] (RTECS)

Isophoronediamine:

RTECS Number:

GV5020833

Inhalation:

Inhalation – Rat TCLo – Lowest published toxic concentration: 200 mg/m³/6H/9D (Intermittent) [Sense organs and special senses (olfaction) – effect, not otherwise specified lung, thorax, or respiration – Structural or functional change in trachea or bronchi lung, thorax, or respiration – other changes] (RTECS)

Phenol, 2,4,6-tris[(dimethylamino)methyl]-:

Eye:

Administration into the eye – Rabbit standard draize test: 50 ug/24H [Severe]

Administration into the eye – Rabbit standard draize test: 50 ug/24H [Severe] (RTECS)

Skin:

Administration onto the skin – Rat LD50 – Lethal dose, 50 percent kill: 1280 mg/kg [Details of toxic effects not reported other than lethal dose value]

Ingestion:

Oral – Rat LD50 – Lethal dose, 50 percent kill: 1200 mg/kg [peripheral nerve and sensation-flaccid paralysis without anesthesia (usually neuromuscular blockage) Lungs, thorax, or respiration-dyspnea]

Oral – Rat LD50 – Lethal dose, 50 percent kill: 1673 mg/kg [Behavioral – tremor gastrointestinal- ulceration or bleeding from the stomach/liver-other changes]

Oral – Rat LD50 – Lethal dose, 50 percent kill: 1200 mg/kg [Perioheral nerve and siation-flaccid paralysis without anesthesia (usually neuromuscular blockage) lungs, thorax, or respiration-dyspnea]

Oral – Rat LD50 – Lethal dose, 50 percent kill: 1673 mg/kg [Behavioral-tremor gastrointestinal- ulceration or bleeding from stomach/liver-other changes] (RTECS)

1,2-Ethanediamine, N1, N2-bis(2-aminoethyl)-:

Eye:

Administration into the eye – Rabbit Standard Draize Test: 49 mg [Severe]

Administration into the eye – Rabbit Standard Draize Test: 20 mg/24H [Moderate] (RTECS)

SpecPoxy Coating Part B

Version 1 pg. 9

Skin:	Administration onto the skin – Rabbit LD50 – Lethal dose, 50 percent kill: 805 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion:	Oral – Rat LD50 – Lethal dose, 50 percent kill: 2500 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
<u>1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-:</u>	
Eye:	Administration into the eye: Rabbit Standard Draize Test: 5 mg [Moderate] Administration into the eye: Rabbit Standard Draize Test: 100 mg/24H [Moderate] (RTECS)

SECTION 12 – ECOLOGICAL INFORMATION

12.2 Persistence and Degradability:	No specific data available on this product.
12.3 Bioaccumulative Potential:	No specific data available on this product.
12.4 Mobility in Soil:	No specific data available on this product.
12.5 Results of PBT and vPvB Assessment:	No specific data available on this product.
12.6 Other Adverse Effects:	No data available
12.7 Water Endangerment Class:	At present, there are no ecotoxicological assessments for this product.

SECTION 13 – DISPOSAL CONSIDERATIONS

<u>13.1 Waste Treatment Methods:</u>	Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations, those of Australia, EU Member States and Japan.
<u>13.2 EU Waste Code:</u>	Not determined

SECTION 14 - TRANSPORTATION INFORMATION

14.1 U.S. Department of Transportation (DOT) Shipping Regulations:
This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN Identification Number:	UN2735
Proper Shipping Name:	Amines Liquid Corrosive NOS (isophoronediamine)
Hazard Class Number and Description:	Class 8 – Corrosive substances
Packing Group:	III
DOT Label(s) Required:	Corrosive substances
North American Emergency Response Guidebook Number:	153

14.2 Environmental Hazards:

SpecPoxy Coating Part B

Version 1 pg. 10

<p>Marine Pollutant:</p> <p>14.3 Special Precaution for User:</p> <p>14.4 International Air Transport Association Shipping Information (IATA):</p> <p>14.5 International Maritime Organization Shipping Information (IMO):</p> <p>UN Identification Number:</p> <p>Proper Shipping Name:</p> <p>Hazard Class Number and Description:</p> <p>Packing Group:</p> <p>EMS-No:</p>	<p>The components of this product are designated by the Department of Transportation to be Marine Pollutants (49 CFR 172.101, Appendix B).</p> <p>None</p> <p>This product is considered as dangerous goods.</p> <p>UN2735</p> <p>Amines Liquid Corrosive NOS (isophoronediamine)</p> <p>Class 8 – Corrosive substances</p> <p>III</p> <p>F-A-S-B</p>
--	---

SECTION 15 – REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations Specific for the Substance or Mixture:

United States Regulations:

U.S. SARA Reporting Requirements:
The components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA 311/312:
Acute Health: Yes; Chronic Health: Yes; Fire: No; Reactivity: No

U.S. CERCLA Reportable Quantity:
Not Applicable

U.S. TSCA Inventory Status:
The components of this product are listed on the TSCA Inventory or are exempted from listing.

Other U.S. Federal Regulations:
None known

California Safe Drinking Water and Toxic Enforcement Act (Proposition 66):
This product does not contain ingredients on the Proposition 65 Lists.

15.2 Canadian Regulations:

Canadian DSL/NDSL Inventory Status:
Components are DSL Listed, NDSL Listed and/or are exempt from listing

Other Canadian Regulations:
Not applicable

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists:
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

Canadian WHMIS Classification and Symbols:
This product is Class E, Corrosive, and D2B, Materials causing other toxic effects, per WHMIS Controlled Product Regulations.



15.3 European Economic Community Information:

SpecPoxy Coating Part B

Version 1

pg. 11

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. See Section 2 for Details.

Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 Australian Information for Product:

Components of this product are listed on the International Chemical Inventory list.

15.5 Japanese Information for Product:

Japanese Minister of International Trade and Industry (MITI) Status: The components of this product are not listed as Class I specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

15.6 International Chemical Inventories:

Listing of the components on individual country Chemical Inventories is as follows:

Australian Inventory of Chemical Substances (AICS): Listed

Korean Existing Chemicals List (ECL): Listed

Japanese Existing National Inventory of Chemical Substances (ENCS): Listed

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Listed

U.S. TSCA: Listed

SECTION 16 – OTHER INFORMATION

Prepared By: Chris Eigbrett (MSDS to GHS Compliance)

Date of Printing: July 1, 2018

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET