

MAX-A-PATCH ACP®

High Performance Asphalt Cold Patch



DESCRIPTION

MAX-A-PATCH ACP® High Performance Asphalt Cold Patch is a high-quality, pre-mixed, all-weather, permanent asphalt cold patch, and the right choice for all types of pavement repair jobs. It can repair dangerous potholes, wide cracks, or ruts within minutes in any type of weather.

MAX-A-PATCH ACP® is ideal for DOT's, municipalities, utility companies, airports and institutional and commercial parking lot maintenance.

FEATURES / BENEFITS

- Self-priming
- All-weather...displaces water
- Permanent repair
- Easy to apply and spread
- Open to traffic immediately after application
- EPP Eligible
- LEED Certifiable with a biodegradable softener
- DOT approved
- Zero VOCs, Contains no diesel or petroleum solvents

APPLICATION

No heating or mixing is required. Remove any unsound substance before applying with a broom or leaf blower.

Simply shovel or pour the patch into the pothole directly from the container.

If the fault is especially deep (over six inches), apply the patch in two-inch layers, compacting in between each layer. Place enough material in the pothole to create a slight "crown."

When completed, compress the patch with a pneumatic tamper. The area can then be opened up to traffic immediately.

Clean-up tools and equipment with SpecChem "Orange Peel" or "Berry Clean".

PACKAGING/COVERAGE

50 lb bag (56 bags per pallet)
Yield per 50 lbs = .41 cu-ft per bag
Example: 4 bags will cover a 10 sq-ft @ 2"



SHELF LIFE / STORAGE

Shelf life of **MAX-A-PATCH ACP®** in the original tightly closed container is 1 year from the date of manufacture.

LIMITATIONS / PRECAUTIONS

- Keep container completely sealed prior to use.
- Keep out of the reach of children.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- Wear protective clothing, goggles and avoid skin contact. Can cause skin irritation upon contact. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed.
- Refer to Safety Data Sheet for complete health and safety information prior to using product.

WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

TECHNICAL SERVICES

For assistance, contact technical services at:
866-791-8700 816-968-5600
www.specchemllc.com



1511 Baltimore Ave, Suite 600
Kansas City, MO 64108
www.specchemllc.com 866.791.8700