

MAX-A-TACK TTC

Trackless Tack Coat Emulsion



DESCRIPTION

MAX-A-TACK TTC is an anionic trackless tack coat emulsion that is used primarily as a tack coat. This product can also be diluted 10% with water and used as a fog seal.

MAX-A-TACK TTC is manufactured to meet applicable state specifications.

FEATURES / BENEFITS

- **Lower application rate** than most conventional tack coats, resulting in application cost savings
- Fast cure time
- Increases bond strength
- Can also be diluted 10% with water and used as a fog seal
- >50% solids
- Zero V.O.Cs

TYPICAL PERFORMANCE DATA

| Specification | Minimum | Maximum |
|----------------------------------|---------|---------|
| Viscosity, seconds (T72) | 0 | 100 |
| Sieve Test, % (T59) | 0.00 | 0.10 |
| Residue by Distillation, % (T59) | 50 | - |
| Oil Distillate, % (T59) | 0 | 3 |
| Penetration (T49) | 0 | 40 |

APPLICATION

Depending on the surface being covered, **MAX-A-TACK TTC** should be applied through a distributor at a **rate of .05 to .10 gallons per square yard** at a temperature of 130°F to 160°F.

Can be applied up to a maximum temperature of 160°F.
Can be applied from pails without heating.

MAX-A-TACK TTC has a minimum "break time" of 10 minutes.



PACKAGING

5 gallon pails (18.9 L)
55 gallon drums (208.2 L)
275 gallon tote (1,041 L)

SHELF LIFE / STORAGE

Shelf life of **MAX-A-TACK TTC** in the original, tightly closed container is six months from the date of manufacture. Optimal storage for MAX-A-TACK TTC is in a heated tank equipped with an agitator at a temperature below 110°F .

LIMITATIONS / PRECAUTIONS

- Do not allow material to freeze
- Avoid extreme overheating
- Keep out of the reach of children.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- Can cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed.
- If eye contact occurs, flush immediately with clean water and seek medical help as needed.
- Refer to Safety Data Sheet for complete health and safety information prior to using product.

FOR WELL VENTILATED OR EXTERIOR USE ONLY!

TECHNICAL SERVICES

For assistance, contact technical services at:
866-791-8700 913-371-8700
www.specchemllc.com



1511 Baltimore Ave, Suite 600
Kansas City, MO 64108
www.specchemllc.com 866.791.8700

WARRANTY

NOTICE-READ CAREFULLY CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.



1511 Baltimore Ave, Suite 600
Kansas City, MO 64108
www.specchemllc.com 866.791.8700