

Rapid Flex Colorant System - Dovetail Gray

Version 1 pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

<p>1.1 Trade Name (as labeled): Synonyms: CAS No:</p> <p>1.2 Product Use:</p> <p>1.3 Company Name: Company Address: Company Address Cont: Business Phone: Website:</p> <p>1.4 Emergency Telephone Number:</p> <p>Date of Last Revision: Date of Current Revision:</p>	<p>Rapid Flex Colorant System – Dovetail Gray N/A Pigment</p> <p>For pigmenting polyurethane and epoxy based coatings, adhesives, sealants, and composites.</p> <p>SpecChem 1511 Baltimore Ave; Suite 600 Kansas City, MO 64108 (816) 968-5600 www.specchemllc.com</p> <p>VelocityEHS 1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)</p> <p>October 3, 2016 July 1, 2018</p>
--	---

SECTION 2 – HAZARDS IDENTIFICATION

<p>US DOT Symbols:</p> <p>EU and GHS Symbols:</p> <p>Signal Word: Hazard Statements: Precautionary Statements:</p>	<p>Not Regulated</p>  <p>Not Applicable Not Applicable Not Applicable</p>
--	--

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.
Titanium Dioxide – Carc. 2, H351	45-55%	13463-67-7
Carbon Black – Carc. 2 H351	<5%	1333-86-4
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).		

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

Rapid Flex Colorant System - Dovetail Gray

Version 1

pg. 2

SECTION 4 – FIRST AID MEASURES

Inhalation:	If inhaled, move to fresh air. Get medical attention if symptoms develop or persist.
Eye Contact:	Rinse immediately with water. Get medical attention if irritation develops or persists.
Skin Contact:	Wash off with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	If swallowed, do not induce vomiting. Give a glass of water. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Notes to Physician:	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Skin may discolor skin due to pigment. Pre- existing skin problems may be aggravated by prolonged or repeated contact. See section 11 for additional information.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, Gaseous extinguishing agents, Fire extinguishing powder, Water fog/Haze. For safety reasons, unsuitable extinguishing agents: Water stream

Fire Fighting: Special protective equipment and precautions for fire-fighters: Wear self-contained breathing apparatus (SCBA) equipped with a full face piece and operated in a pressure demand mode (or other positive pressure mode) and approved protective clothing.

Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, where SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations. See section 9 for additional information.

Protection of Firefighters: Wear positive pressure self-contained breathing apparatus (SCBA) and approved protective clothing (helmet, coat, trousers, boots and gloves). If contact is likely, use full chemical resistant fire fighting clothing with SCBA.

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

Water Spill: Keep material out of storm sewers and ditches which lead to waterways. Contain spilled material with sand or earth. Clean up spill immediately, observing precautions in the Personal Protection Section of SDS.

Land Spill: Isolate hazard area and deny entry to unnecessary or unprotected personnel. Contact applicable authorities and determine applicable regulations based on SDS information.

Air Release: Contact applicable authorities and determine applicable regulations based on SDS

Rapid Flex Colorant System - Dovetail Gray

Version 1 pg. 3

information.

Methods of Containment and Clean Up: Take up mechanically and dispose of according to local, state and federal regulations. For small amounts, absorb with a liquid binding material such as diatomaceous earth and dispose of according to local, state and federal regulations. Contain large amounts and pump up into suitable containers. Clean any slippery coating that remains using a detergent/soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

SECTION 7 - HANDLING AND STORAGE

Handling: As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing.

Storage: This material is not hazardous under normal storage conditions; however, material should be stored in closed containers, in a secure area to prevent container damage and subsequent spillage. It is recommended that containers be raised above floor or ground during extended storage periods to prevent container corrosion due to standing water. Do not store in open, unlabeled or mislabeled container. Keep container closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Titanium Dioxide	Not Established	Not Established	Not Established
Carbon Black	Not Established	Not Established	Not Established

Engineering Controls: Investigate engineering techniques to reduce exposures. Provide ventilation if necessary to minimize exposures. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

General Hygiene Considerations: Wear Gloves.

Eye/face Protection: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas. Use good industrial practice to avoid eye contact.

Skin Protection: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Minimize skin contamination by following good industrial hygiene practice. Wash hands and contaminated skin thoroughly after handling. Use good personal hygiene when handling this product. Wash hands after use, before

Rapid Flex Colorant System - Dovetail Gray

Version 1

pg. 4

eating, drinking, smoking, or using the toilet.

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators air respirators May be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties:

Appearance (Physical State and Color): Medium Gray/Liquid

Odor: Mild

Odor Threshold: No data available

pH: Approx. 6

Melting/Freezing Point: No data available

Boiling Point: >199°C (>390°F)

Flash Point: 204 °C (399.2°F)

Evaporation Rate: No data available

Flammability (Solid; Gas): No data available

Upper/Lower Flammability or Explosion Limits: No data available

Vapor Pressure (mm Hg @ 20°C (68° F): <0.0013 hPa (<0mm Hg) (<0.001 mm Hg)

Vapor Density: 1.67g/cm³ (14.0 lbs/gal)

Relative Density: No data available

Specific Gravity: No data available

Solubility in Water: Slightly soluble

Weight per Gallon: No data available

Partition Coefficient (n-octanol/water): No data available

Auto-Ignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: 3,000 cP (+/- 900) at Room Temperature

9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability: This material is chemically stable under specified conditions or storage, shipment and/or use.

Incompatible Materials: No further relevant information available.

Products of Combustion: No further relevant information available.

Hazardous Decomposition Products: Possible in traces.

Possibility of hazardous reactions: Reacts with strong oxidizing agents. Toxic fumes maybe released if heated above the decomposition point.

Rapid Flex Colorant System - Dovetail Gray

Version 1

pg. 5

SECTION 11 – TOXICOLOGY INFORMATION

Mixture Toxicity:

Inhalation Toxicity LC50: None

Component Toxicity Likely Routes of Exposure:

No data found

Effects of Overexposure:

NTP (National Toxicology Program): None of the ingredients listed

OSHA-Ca (Occupational Safety and Health Administration: None of the ingredients listed.

Probable Routes of Exposure:

Ingestion, inhalation, eye contact, skin contact.

Acute effects (acute toxicity, irritation and corrosivity from products as supplied: None

Repeated dose toxicity: No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity based on available data: The classification criteria are not met.

Carcinogenicity: Contains known or suspect carcinogens when inhaled. Product is in a non-inhalable form and is non-classifiable as a carcinogen.

Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12 – ECOLOGICAL INFORMATION

General note: Do not allow undiluted product or large quantities of it reach ground water, water course or sewage system.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with federal, state and local regulations. Smaller quantities can be disposed of with household waste.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 U.S. Department of Transportation (DOT) Shipping Regulations:

This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN Identification Number: Not Regulated

Proper Shipping Name: None

Rapid Flex Colorant System - Dovetail Gray

Version 1

pg. 6

Hazard Class Number and Description:	None
Packing Group:	None
DOT Label(s) Required:	None
North American Emergency Response Guidebook Number:	None
14.2 Environmental Hazards:	
Marine Pollutant:	None
14.3 Special Precaution for User:	None
14.4 International Air Transport Association Shipping Information (IATA):	None
14.5 International Maritime Organization Shipping Information (IMO):	
UN Identification Number:	Not regulated
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
EMS-No:	None

SECTION 15 – REGULATORY INFORMATION
US/CANADA REGULATORY INFORMATION:

WHMIS (Canada) Status: This is not a WHMIS controlled product.

TSCA Inventory Status & TSCA Information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical substance Inventory.

TSCA 12 (b) Export Notification:

This material does not contain any TSCA 12 (b) regulated chemicals.

CERCLA REGULATED CHEMICALS:

This material does not contain any CERCLA regulated chemicals

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substance.

SARA 311 / 312 Hazard Class:

This product does not contain any SARA 311/312 hazardous substance.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above the minimum levels.

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

CALIFORNIA PROPOSITION 65:

This product contains Titanium dioxide, CAS# 13463-67-7 and Carbon black, CAS#1333-86-4 known to the state of California to cause cancer, birth defects, or any other reproductive harm but in a non-respirable form not the powder state as cited in the

Rapid Flex Colorant System - Dovetail Gray

Version 1

pg. 7

proposition.

Reference to Titanium dioxide and Carbon black is based on unbound respirable particles and is not generally applicable to the product as supplied.

SECTION 16 – OTHER INFORMATION

Date of Printing: July 1, 2018

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET

Rapid Flex Colorant System - Grizzly Gray

Version 1 pg. 1

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

<p>1.1 Trade Name (as labeled): Synonyms: CAS No:</p> <p>1.2 Product Use:</p> <p>1.3 Company Name: Company Address: Company Address Cont: Business Phone: Website:</p> <p>1.4 Emergency Telephone Number:</p> <p>Date of Last Revision: Date of Current Revision:</p>	<p>Rapid Flex Colorant System – Grizzly Gray N/A Pigment For pigmenting polyurea and epoxy joint fillers, coatings, and adhesives.</p> <p>SpecChem 1511 Baltimore Ave; Suite 600 Kansas City, MO 64108 (816) 968-5600 www.specchemllc.com</p> <p>VelocityEHS 1-(800)255-3924 (North America) +1-813-248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)</p> <p>October 3, 2016 July 1, 2018</p>
--	---

SECTION 2 – HAZARDS IDENTIFICATION

<p>US DOT Symbols:</p> <p>EU and GHS Symbols:</p> <p>Signal Word: Hazard Statements: Precautionary Statements:</p>	<p>Not Regulated</p>  <p>Not Applicable Not Applicable Not Applicable</p>
--	--

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	WT%	CAS No.
Titanium Dioxide – Carc. 2, H351	30-40%	13463-67-7
Carbon Black – Carc. 2 H351	<5%	1333-86-4
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).		

Note: All WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2010 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard JIS Z 7250:2000

SECTION 4 – FIRST AID MEASURES

Rapid Flex Colorant System - Grizzly Gray

Version 1

pg. 2

Inhalation:	If inhaled, move to fresh air. Get medical attention if symptoms develop or persist.
Eye Contact:	Rinse immediately with water. Get medical attention if irritation develops or persists.
Skin Contact:	Wash off with soap and water. Get medical attention if irritation develops or persists.
Ingestion:	If swallowed, do not induce vomiting. Give a glass of water. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Notes to Physician:	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Skin may discolor skin due to pigment. Pre- existing skin problems may be aggravated by prolonged or repeated contact. See section 11 for additional information.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, Gaseous extinguishing agents, Fire extinguishing powder, Water fog/Haze. For safety reasons, unsuitable extinguishing agents: Water stream

Fire Fighting: Special protective equipment and precautions for fire-fighters: Wear self-contained breathing apparatus (SCBA) equipped with a full face piece and operated in a pressure demand mode (or other positive pressure mode) and approved protective clothing.

Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, where SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations. See section 9 for additional information.

Protection of Firefighters: Wear positive pressure self-contained breathing apparatus (SCBA) and approved protective clothing (helmet, coat, trousers, boots and gloves). If contact is likely, use full chemical resistant fire fighting clothing with SCBA.

SECTION 6 – ACCIDENTAL RELEASE MEASURES (STEPS FOR SPILLS)

Water Spill: Keep material out of storm sewers and ditches which lead to waterways. Contain spilled material with sand or earth. Clean up spill immediately, observing precautions in the Personal Protection Section of SDS.

Land Spill: Isolate hazard area and deny entry to unnecessary or unprotected personnel. Contact applicable authorities and determine applicable regulations based on SDS information.

Air Release: Contact applicable authorities and determine applicable regulations based on SDS information.

Rapid Flex Colorant System - Grizzly Gray

Version 1 pg. 3

Methods of Containment and Clean Up: Take up mechanically and dispose of according to local, state and federal regulations. For small amounts, absorb with a liquid binding material such as diatomaceous earth and dispose of according to local, state and federal regulations. Contain large amounts and pump up into suitable containers. Clean any slippery coating that remains using a detergent/soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

SECTION 7 - HANDLING AND STORAGE

Handling: As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing.

Storage: This material is not hazardous under normal storage conditions; however, material should be stored in closed containers, in a secure area to prevent container damage and subsequent spillage. It is recommended that containers be raised above floor or ground during extended storage periods to prevent container corrosion due to standing water. Do not store in open, unlabeled or mislabeled container. Keep container closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Parameters:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Titanium Dioxide	Not Established	Not Established	Not Established
Carbon Black	Not Established	Not Established	Not Established

Engineering Controls: Investigate engineering techniques to reduce exposures. Provide ventilation if necessary to minimize exposures. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

General Hygiene Considerations: Wear Gloves.

Eye/face Protection: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas. Use good industrial practice to avoid eye contact.

Skin Protection: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Minimize skin contamination by following good industrial hygiene practice. Wash hands and contaminated skin thoroughly after handling. Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

Rapid Flex Colorant System - Grizzly Gray

Version 1

pg. 4

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators air respirators May be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties:

Appearance (Physical State and Color): Dark Gray/Liquid

Odor: Mild

Odor Threshold: No data available

pH: Approx. 6

Melting/Freezing Point: No data available

Boiling Point: >199°C (>390°F)

Flash Point: 204 °C (399.2°F)

Evaporation Rate: No data available

Flammability (Solid; Gas): No data available

Upper/Lower Flammability or Explosion Limits: No data available

Vapor Pressure (mm Hg @ 20°C (68° F): <0.0013 hPa (<0mm Hg) (<0.001 mm Hg)

Vapor Density: 1.56 g/cm³ (14.0 lbs/gal)

Relative Density: No data available

Specific Gravity: No data available

Solubility in Water: Slightly soluble

Weight per Gallon: No data available

Partition Coefficient (n-octanol/water): No data available

Auto-Ignition Temperature: No data available

Decomposition Temperature: No data available

Viscosity: 7,400 cP (+/- 2,240) at Room Temperature

9.2 Other Information: No data available

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability: This material is chemically stable under specified conditions or storage, shipment and/or use.

Incompatible Materials: No further relevant information available.

Products of Combustion: No further relevant information available.

Hazardous Decomposition Products: Possible in traces.

Possibility of hazardous reactions: Reacts with strong oxidizing agents. Toxic fumes maybe released if heated above the decomposition point.

Rapid Flex Colorant System - Grizzly Gray

Version 1

pg. 5

SECTION 11 – TOXICOLOGY INFORMATION

Mixture Toxicity:

Inhalation Toxicity LC50: None

Component Toxicity Likely Routes of Exposure:

No data found

Effects of Overexposure:

NTP (National Toxicology Program): None of the ingredients listed

OSHA-Ca (Occupational Safety and Health Administration): None of the ingredients listed.

Probable Routes of Exposure:

Ingestion, inhalation, eye contact, skin contact.

Acute effects (acute toxicity, irritation and corrosivity from products as supplied: None

Repeated dose toxicity: No further relevant information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity based on available data: The classification criteria are not met.

Carcinogenicity: Contains known or suspect carcinogens when inhaled. Product is in a non-inhalable form and is non-classifiable as a carcinogen.

Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12 – ECOLOGICAL INFORMATION

General note: Do not allow undiluted product or large quantities of it reach ground water, water course or sewage system.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with federal, state and local regulations. Smaller quantities can be disposed of with household waste.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 U.S. Department of Transportation (DOT) Shipping Regulations:

This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

UN Identification Number: Not Regulated

Proper Shipping Name: None

Hazard Class Number and Description: None

Packing Group: None

Rapid Flex Colorant System - Grizzly Gray

Version 1

pg. 6

DOT Label(s) Required:	None
North American Emergency Response Guidebook Number:	None
<u>14.2 Environmental Hazards:</u>	
Marine Pollutant:	None
<u>14.3 Special Precaution for User:</u>	None
<u>14.4 International Air Transport Association Shipping Information (IATA):</u>	None
<u>14.5 International Maritime Organization Shipping Information (IMO):</u>	
UN Identification Number:	Not regulated
Proper Shipping Name:	None
Hazard Class Number and Description:	None
Packing Group:	None
EMS-No:	None

SECTION 15 – REGULATORY INFORMATION
US/CANADA REGULATORY INFORMATION:

WHMIS (Canada) Status: This is not a WHMIS controlled product.

TSCA Inventory Status & TSCA Information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical substance Inventory.

TSCA 12 (b) Export Notification:

This material does not contain any TSCA 12 (b) regulated chemicals.

CERCLA REGULATED CHEMICALS:

This material does not contain any CERCLA regulated chemicals

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substance.

SARA 311 / 312 Hazard Class:

This product does not contain any SARA 311/312 hazardous substance.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above the minimum levels.

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

CALIFORNIA PROPOSITION 65:

This product contains Titanium dioxide, CAS# 13463-67-7 and Carbon black, CAS#1333-86-4 known to the state of California to cause cancer, birth defects, or any other reproductive harm but in a non-respirable form not the powder state as cited in the proposition.

Rapid Flex Colorant System - Grizzly Gray

Version 1

pg. 7

Reference to Titanium dioxide and Carbon black is based on unbound respirable particles and is not generally applicable to the product as supplied.

SECTION 16 – OTHER INFORMATION

Date of Printing: July 1, 2018

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. This safety sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. SpecChem assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, SpecChem assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.

END OF SDS SHEET