

PERMA TILE GROUT

Non-Yellowing Fade Resistant Tile Grout

DESCRIPTION

PERMA TILE GROUT is a special blend of Portland cements, fortifiers and graded fillers.

PERMA TILE GROUT is suitable for all grouting applications in the areas of floor and wall tile, shower stalls, towel rack and soap dishes, sink tops and mosaic tile applications.

FEATURES/BENEFITS

- Mix with water only
- Produces a strong and durable grout joint
- Remains chip, shrink, stain and water resistant
- Bright white, non-yellowing and fade resistant
- May be tinted to match tile

APPLICATION

Surface Preparation: For new installations allow the tile to set for 18 to 24 hours prior to proceeding with grouting. Tile and grout joints should be clean and free from any dust or adhesive. For re-grouting of old joints you must remove all dead or unsound grout with a grout joint saw. Wipe the surface with a damp cloth to remove any dust or dried soap from the tile and joint areas. No priming is required.

MIXING AND APPLICATION:

Add clean water to a mixing pail and gradually add the PERMA TILE GROUT to the pail while mixing. Continue to mix and add grout until a soft paste consistency is achieved. Let stand for 15 minutes and then re-temper. A small amount of additional water may be needed.

Apply PERMA TILE GROUT with a rubber grout float held at a 30° angle. Work grout into the joints with strokes at 45° angle to the grout joints. Work in material until all gaps and air pockets have been removed. Remove excess material with grout float and move onto an adjoining area. Work in small areas that can be completed in 15 to 20 minutes.

APPLICATION NOTES:

1. PERMA TILE GROUT should be cured by misting with water at least once in the first 24 hours.
2. Suitable for new or restoration work
3. Dispose of waste materials in accordance with Federal, State and local regulations
4. The use of a dust mask, safety goggles and rubber gloves are recommended.
5. Caution: Contains Portland Cement which is highly caustic
6. In case of contact, flush eyes with water. Wash skin with soap and water. Consult a physician

PACKAGING

5 lb Tubs 8/Case
3000 lb Super-Sacks

SHELF LIFE

1 year when stored in original unopened container

WARRANTY

NOTICE-READ CAREFULLY

CONDITIONS OF SALE

SpecChem offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of SpecChem. No other representative of or for SpecChem is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

SpecChem warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, SpecChem will replace the defective product with new product without charge to the purchaser. SpecChem makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.

SPECCHEM 
Solution to Service

1511 Baltimore Ave, Suite 600
Kansas City, MO 64108

www.specchemllc.com

866.791.8700